



The Adhesive Company



April 5, 2010

Dear Bostik Customer:

Congratulations for your forward thinking and the environmentally conscious design of your current construction project. Bostik is pleased to be a U.S. Green Building Council member and a major proponent of the LEED initiative in the construction materials industry.

Bostik is a leader in the adhesive, sealant and coatings segment of the construction market with one of the most comprehensive product offerings available, all backed by strong system warranties. Bostik is the 4th largest adhesive and sealant company in the world. The greatest advantage of utilizing all of our products for your flooring system and construction sealants/adhesives is that you have only one manufacturer to deal with if questions or concerns arise. Additionally, we have a dedicated sales and technical service organization that is at your service any time you need assistance.

Attached is a complete list of the Bostik products that may contribute to the qualifications of a project for LEED-NC V2.2 certification under the following Indoor Environmental Quality credits for low emitting materials: EQ 4.1 Adhesives & Sealants, EQ 4.2 Paints & Coatings and EQ 4.3 Carpet Systems. (An extract of these standards is attached for your review.) The intent of these one-point credits is to reduce the quantity of indoor air contaminants that are odorous, potentially irritating and/or harmful to the comfort and well-being of installers and occupants.

If you have any questions regarding our product offering, please contact Bostik directly at 800-7/BOSTIK. Once again, we look forward to working with you on this exciting project.

Regards,
Scott J. Banda

A handwritten signature in black ink, appearing to read "S. J. Banda".


Market Manager
LEED Accredited Professional

Bostik, Inc.
Construction & Distribution Division
211 Boston Street
Middleton, MA 01949-2128 USA
Tel: 978.777.0100 - Fax: 978.750.7802
www.bostik-us.com



Low-VOC Product Portfolio
Adhesives/Sealants/Coatings



Durabond® Hardwood Products	Product %-VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %			g/L	
Moisture Vapor Protection				
D-288™ Moisture Vapor Retarder	8.3	N/A	126	250
Hardwood Adhesives				
D-332™ Premium Wood Flooring Adhesive	5.8	15	86	100
D-321™ Moisture Cure Urethane Adhesive	0	15	0	100
D-317™ Elastomeric Wood Flooring Adhesive	8.0	15	85	100
Durabond® Ceramic Products	Product %-VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %			g/L	
Waterproofing & Antifracture Membrane				
D-222 DuraGuard™ Waterproofing Membrane	1.1	N/A	12.5	250
Grouts/Epoxies				
TruColor™ Pre-Mixed Grout 	2.1	N/A	35	65
D-190 DuraPoxy™ Epoxy-Modified Grout and Mortar Admixture	0	N/A	0	65
EzPoxy™ 100% Solids Epoxy Grout & Mortar	0	N/A	0	65
Fortified Tile Grout Sanded	0	N/A	0	65
Fortified Tile Grout (Unsanded)	0	N/A	0	65
Liquid Admixtures				
D-L16™ High Strength Mortar and Grout Additive	0	N/A	0	65
Thin Set Mortars				
D-70™ ProFlex	0	N/A	0	65
D-65™ High Performance & Non Sag Mortar	0	N/A	0	65
D-60™ Medium Set	0	N/A	0	65
D-55™ Fast Set	0	N/A	0	65
D-50™ Flexible	0	N/A	0	65
D-40™ DuraFlex	0	N/A	0	65
D-25™ DitraSet	0	N/A	0	65
D-20™ Porcelain Set	0	N/A	0	65
D-5™ Premium	0	N/A	0	65
D-2™ Floor Grade	0	N/A	0	65

 Contains recyclable/renewable materials.




Durabond® Floor Covering Products	Product %-VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %			g/L	
Moisture Vapor Barrier Coatings				
D-261™ Extreme Moisture Vapor Barrier Coating	4.0	N/A	59	250
D-250™ Moisture Vapor Barrier Coating	5.0	N/A	67	250
Specialty Adhesives				
GreenFusion™ One-Component, Trowel Applied Rubber Flooring, Urethane Adhesive	0	15	0	60
GreenFusion2™ Two-Component, Trowel Applied Rubber Flooring, Urethane Adhesive 	0	15	0	60
Multipurpose Adhesive				
D-990™ Multipurpose Adhesive	0	15	0	50
D-920™ Multipurpose Adhesive	0	15	0	50
D-910™ Multipurpose Adhesive	0	15	0	50
D-905™ Multipurpose Adhesive	0	15	0	50
Carpet Adhesives				
D-870™ Carpet Tile & Pad Adhesive	0	15	0	50
D-860™ Double Stick Adhesive	0	15	0	50
D-850™ Carpet Adhesive	0	N/A	0	50
D-818™ Tack Strip & Multipurpose Adhesive	3.9	15	48	50
D-817™ Carpet Pad Adhesive	1.0	15	17	50
D-808™ Exterior Carpet Adhesive	0	15	0	50
Wall Surface				
D-745™ Fire Retardant Wall Adhesive	0.9	15	15	50
D-740™ Multipurpose Wall Adhesive	1.7	15	39	50
Hard Surface				
D-670™ Firm Set Goods and Carpet Adhesive	0	15	0	50
D-650™ Clear VCT Adhesive	0	15	0	50
D-640™ Pure Vinyl Adhesive	0	15	0	50
Primers				
Durabond® Extreme Primer	<1	N/A	7.7	250
Durabond® Patches and Underlayments	Product %-VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %			g/L	
Self Leveling Underlayments				
DuraLevel® 83P™ Self-Leveling Underlayment	0	N/A	0	N/A
Patches				
Bostik® UltraFinish™	0	N/A	0	N/A
Webcrete® 95	0	N/A	0	N/A
Webcrete® 98	0	N/A	0	N/A
Webpatch 90	0	N/A	0	N/A
D-9001 Webpatch	0	N/A	0	N/A



Hydroment® Ceramic Products	Product %-VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %		g/L		
Waterproofing & Antifracture Membranes				
Gold™ Waterproofing Membrane	1.1	N/A	12.5	250
Black-Top™ 90210 Liquid Applied, Fabric-reinforced Waterproofing and Crack Isolation Membrane	N/A	N/A	31	250
UltraSet® Advanced Antifracture Waterproofing, Crack Isolation and Sound Reducing Membrane	7.9	N/A	134	250
Grouts/Epoxies				
TruColor™ Pre-Mixed Grout	2.1	N/A	35	65
1900™ Epoxy-Modified Grout and Mortar Admixture	0	N/A	0	65
EzPoxy™ 100% Solids Epoxy Grout & Mortar	0	N/A	0	65
Ceramic Tile Grout (Sanded)	0	N/A	0	65
Ceramic Tile Grout (Unsanded)	0	N/A	0	65
Liquid Admixtures				
425 High Strength Mortar and Grout Additive	0	N/A	0	65
447 Flex-A-Lastic Admixture	0	N/A	0	65
Thin Set Mortars				
ReFlex®	0	N/A	0	65
StoneWall™ High Performance & Non Sag Mortar	0	N/A	0	65
Big Tile & Stone™	0	N/A	0	65
Single Flex® FS	0	N/A	0	65
Single Flex®	0	N/A	0	65
Hydroment PM	0	N/A	0	65
Ditra-Set™	0	N/A	0	65
Porcelain-Mate™	0	N/A	0	65
Tile-Mate®	0	N/A	0	65
Tile-Mate® Floor & Wall	0	N/A	0	65
Bostik® Patches and Underlayments	Product %-VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %		g/L		
Self Leveling Underlayments				
SL-150™ Self Leveling Underlayment	0	N/A	0	N/A
Patches				
Bostik® UltraFinish™	0	N/A	0	N/A
Fast Patch 102	0	N/A	0	N/A
Primers				
Universal Primer	1.2	N/A	15	250



Bostik Hardwood Products	Product %-VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %		g/L		
Moisture Vapor Protection				
MVP™ Moisture Vapor Barrier Coating	8.3	N/A	126	250
EMC™ Epoxy Moisture Coating	5.0	N/A	67	100
Adhesives				
Vapor-Lock™ Urethane Adhesive and Vapor-Retarding Membrane	0	15	0	100
ULTRA-SET® SingleStep™ 	0	15	0	100
Bostik's Best	5.8	15	86	100
TKO™ (New & Improved)	0	15	0	100
BST™	4.6	15	72	100
EFA+ (Elastomeric Flooring Adhesive)	8.0	15	85	100
HPL™ (High Performance Latex) Adhesive	< 1%	15	< 11 g/L	100



Chem-Calk® Products	Product %-VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC LEED- NC/ LEED-H Standard (SCAQMD VOC levels)
Weight %		g/L		
Construction Adhesives & Sealants				
Chem-Calk® 900 Architectural Grade Urethane Sealant	3.9	4	48	250
Chem-Calk® 915 Construction Grade Urethane Sealant	3.9	4	53	250
Chem-Calk® 916 Textured Urethane Sealant	3.9	4	53	250
Chem-Calk® GPS1 General Purpose Urethane Sealant	2.4	4	51	250
Chem-Calk® 955-SL Self-Leveling Sealant	3.9	4	51	250
Chem-Calk® 2020 Architectural Grade Hybrid Sealant	1.1	4	16	250
Chem-Calk® 2000 Construction Grade Hybrid Sealant	1.4	4	21	250
Chem-Calk® 505 Non-Sag, 2-Component Polyurethane Sealant	1.7	4	25	250
Chem-Calk® 1250 Oxime/Neutral Cure Silicone Sealant	2.0	15	30	250
Chem-Calk® 1200 General Purpose Silicone Sealant	2.0	15	28	250
Chem-Calk® 1200-HT High Temperature, RTV, Acetoxy-(Acid) Cure Silicone Sealant	2.0	15	< 30	250



Bostik HOME® PRODUCTS	Product %-VOC	NAHB Model Green Home Guideline (based upon CARB VOC levels)	Product VOC g/L	USGBC L.E.E.D H System (based upon SCAQMD VOC levels)
		Weight %	g/L	
Construction Adhesives & Sealants				
Heavy Duty Construction Adhesive	6.9	15	105	50
Painters Caulk	2	15	33	250
Siliconize Acrylic Latex Sealant	2	15	32	250

Bostik, Inc.
211 Boston Street
Middletown, MA 01949

Customer Service and
Technical Service:
1-800-7BOSTIK

Websites:
www.bostik-us.com
www.greenmission.bostik-us.com

