



TECHNICAL DATA SHEET

Bostik® TOPCOTE® Saw Table & Tool Surface Sealant

Date of Last Revision: 02/16/09

Product Description

Regular maintenance of saw tables and receiving tables with Bostik® TopCote® significantly reduces sliding friction on all metal, laminate, and plastic surfaces.

Product Benefits

- Eliminates "hang-ups" on sliding surfaces.
- Protects all tools and equipment from rust.
- Up to 30% slicker than paste wax.
- Easier and quicker to apply than paste wax.
- Lasts three times (3x) longer than paste wax.
- Contains no silicone or petroleum oil. Will not stain wood or interfere with glues or finishes.
- Perfect for table saw beds, drill presses, lathes, planers, band saws, miters, panel saws, and all hand tools.
- Environmentally safer aerosol, no CFC's or ODC's
- Bostik TopCote® Meets or Exceeds Federal, State, and Local VOC standards for Voc Content, including EPA, CARB, AQMDs and OTC.

Directions

To Reduce Friction:

Clean saw table or tool surfaces thoroughly with a degreasing agent (i.e., lacquer thinner). Spray a thin, even coat over entire surface. Allow a few seconds to dry to a haze. Rub in lightly with a clean, dry cloth. After a few minutes, buff to a shine.

For Best Results:

Re-spray a second coat. Reapply weekly or more frequently based on work load.



Applications

Wood Working

- Table saw
- Panel saws
- Gang rip saws
- Jointers
- Shapers
- Band saws
- Edgers
- Pneumatic Tools:
 - Slide magazine
 - Feed mechanism
 - Nosepiece
 - Feed spring

Other

- Release Agent For:
 - Injection molds
 - Printing plates
- Printing & Binding Uses:
 - Sliding surfaces
 - Conveyor rollers

Product Specifications

Container	Net Weight	Case Pack	Case Weight
Aerosol	5.5 oz.	12	7.1 lbs.
Aerosol	10.75 oz.	12	12.2 lbs.

Bostik, Inc.

211 Boston Street
 Middleton, MA 01949 USA
 TEL. 888-603-8558
 FAX 978-750-7293
<http://www.bostik-us.com>

IMPORTANT NOTICE

All statements, technical information and recommendations set forth herein are based on tests which Bostik, Inc. believes to be reliable. However, Bostik, Inc. does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sales of this product shall be on terms and conditions set forth on Bostik's order acknowledgment. Bostik, Inc. warrants that the product conforms with Bostik written specifications, and is free from defects. BOSTIK, INC. DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NON-COMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK BE LIABLE FOR DIRECT, CONSEQUENTIAL ECONOMIC OR OTHER DAMAGES.